COVID-19 Business Restart Lorry Crane Checklist – TRUCK

Illustration	Step Description	Checked (Y/N)
	Engine oil Before starting the truck look beneath it for any oil spills or leaks Check the engine oil level and top up if necessary	(1710)
	- Top up if necessary	
	Brake and clutch fluid levels - Check as a precaution	
	Fan and aircon belts - Check for any worn out and tension	
	Tires - Check the air pressure for the wheels	
	Spray WD-40 Liberally spray it in the engine compartment and on all electrical connectors as it will remove moisture and rust This will help to lubricate everything it is sprayed on and the flow of electric currents	

<u>Illustration</u>	Step Description	Checked (Y/N)
Baller	- In case the battery has drained, the vehicle should be jump started	
	- Check and refill if necessary	
	Condition of the air filter - Clean it if necessary	

COVID-19 Business Restart Lorry Crane Checklist – LOADER CRANE

<u>Illustration</u>	Step Description & Notes	Checked
		<u>(Y/N)</u>
	- Clean the crane surface thoroughly	
A CONTRACTOR OF THE PARTY OF TH	Oil level in oil tank - Top up if necessary	
	Oil purity - Replace the oil if its contaminated or filled with grime or dirt	
	High-pressure filter - Check through the condition thoroughly	
	Return filter and air filter (tank) - Check the condition and replace if necessary	
	Hydraulic hoses and tubes Check the condition for cuts, cracks and damage	

<u>Illustration</u>	Step Description & Notes	Checked
	Electrical cables Check the condition for cuts, abrasions and cracks	<u>(Y/N)</u>
	Steel parts - Check for any rust or corrosion	
	Check the condition for traces of insufficient lubrication, contamination & broken strands, replace if damaged	
	Remove all the old, dirty grease and contamination from the lubricating points	
	Press the grease into the lubricating point. Move the components, this distributes the grease inside, press more grease until the fresh grease comes out of the bearing point	