


MBB R 1500 S



- 1500 kg Tragkraft mit 4 Zylindern bei 1000 mm Lastabstand
- Einfach gefaltete Plattform
- Modulare und schraubbare Bauweise zur Anpassung an verschiedenste Fahrzeugtypen
- Ausführung der Plattform in Vollaluminium- oder Stahl/Alu
- Federunterstütztes Faltteil
- Plattformpaket dient als Unterfahrschutz
- Überfahrnase für Drehstangenverschlüsse
- Antriebsstarker Verfahrzylinder für die horizontale Positionierung der Hubladebühne
- Optimale Anpassung an Motorwagen und Anhänger durch eine Vielzahl verschiedener Lenkerlängen und Stichmaße
- Verfahrsschienen standardmäßig in Stahl, optional in Aluminium erhältlich
- Optional vollständig vormontiert und mit Energiekette lieferbar

LOAD DIAGRAM

| a (mm) | Q (kg) |
|--------|--------|
| 1,000 | 1,500 |
| 1,200 | 1,250 |
| 1,500 | 1,000 |
| 1,850 | 800 |




THE RETRACTABLE TAIL LIFT WITH 1,500 KG LIFTING CAPACITY

WEIGHTS

| | |
|-----------------------------------|--------|
| Aluminium/aluminium platform type | |
| Platform width (mm) | 2,400 |
| Platform height (mm) | |
| 1,805 | 665 kg |

WEIGHTS

| | |
|-------------------------------|--------|
| Steel/aluminium platform type | |
| Platform width (mm) | 2,400 |
| Platform height (mm) | |
| 1,800 | 770 kg |



DIMENSIONS

| | | | | | |
|---|-------|-------|-------|-------|-------|
| Lifting arm lengths (mm) | 700 | 800 | 900 | 1,000 | 1,100 |
| H (max.) loading height, unloaded | 1,200 | 1,428 | 1,548 | 1,651 | 1,793 |
| H (min.) loading height, loaded | 883 | 916 | 1,006 | 950 | 1,023 |
| F (max.) middle of main beam to upper edge of loading floor | 650 | 817 | 924 | 977 | 1,056 |
| K (min.) at dimension F (max.) | 618 | 601 | 623 | 721 | 783 |
| D (min.) installation dimension, minimum | 1,800 | 1,800 | 1,900 | 1,900 | 2,000 |
| F (min.) | 508 | 566 | 614 | 569 | 608 |
| K (max.) at dimension F (min.) | 726 | 820 | 907 | 1,040 | 1,132 |
| G (max.) unloaded (middle of main beam to ground) | 550 | 611 | 624 | 674 | 737 |
| G (min.) loaded | 375 | 350 | 392 | 381 | 415 |
| E (max.) vehicle frame width (max.) | 920 | 920 | 920 | 920 | 920 |
| E (min.) vehicle frame width (min.) | 645 | 645 | 645 | 645 | 645 |

TECHNICAL DATA

| | |
|-----------------------------------|---|
| Type | MBB R 1500 S |
| Lifting capacity | 1,500 kg |
| Main beam | 180 x 180 mm |
| Lifting gear hydraulics | 2 lifting cylinders / 2 tilting cylinders / 1 moving cylinder |
| Lifting arm pitch | 750/1,300/1,480 mm |
| Load centre, longitudinal | 1,000 mm |
| Load centre, across centre | Central, 50% of rated load on one side |
| Inclination angle of the platform | +10° to -10° |

Some of the tail lifts pictured feature special customer-specific equipment. Country-specific regulations must be considered for the tail lift installation. Dimensions may vary. Subject to technical changes, errors and translation mistakes.

