



Palfinger Europe GmbH
Mr. Gerhard Luger
Moosmühlstr. 1
5203 Köstendorf
AUSTRIA

Stefan Lochner
Dachauer Strasse 667
D-80995 München
Germany
E-mail: stefan.lochner@man.eu

Your tel: E-Mail: ESA CRM GP No. Your reference: 06.07.2021
PK 24001 SLD-Kran-Kipper

Offer number: 202100299539

Specification for Quotation:1154-2021-000 TKS "Europe_10" Aufbau: PK 24001 SLD Kran-Kipper

5897c3df-ab6c-4055-8da6-bc316686f02f

/opt/invaris/dcs/resources/mit-ep3_produktion_produktion/mit-ep3/texts/zyenf.rtf



Vehicle description for: TGS 28.510 6x4-4 BL CH



Illustration can deviate

Vehicle standards

Product family	The new MAN Truck Generation
Variant designation	TGS 28.510 6x4-4 BL CH
MAN code	2MNEGOX
Vehicle type	Vehicle type Tipper (KI)
Cab	Local transport cab NN
Main wheel distance	3600 mm
Overhang	800 mm
Steering configuration	Left

Vertical Load

	National Registration	Technical Load
Gross weight	26,000 kg	28,000 kg
Front axle	9,000 kg	9,000 kg
Rear axle	11,500 kg	12,000 kg
Trailing axle	7,500 kg	8,000 kg

Horizontal Load

	National Registration	Technical Load
Trailer Load	24,000 kg	40,000 kg
Gross train weight	40,000 kg	68,000 kg

5897c3df-ab6c-4055-8da6-bc316686f02f



The printed images in this offer are for explanatory purposes and may differ from the actual configuration.
For further product information on the tire selection "selectively", please contact our sales staff.

Vehicle characteristics

Basic characteristics

<input type="checkbox"/>	Chassis	0P2U9
<input type="checkbox"/>	Chassis class, heavy	0P2UC
<input type="checkbox"/>	Destination: Germany (DE)	0P3GA
<input type="checkbox"/>	Merchant tonnage 28 t	0P8LI
<input type="checkbox"/>	Basic layout of vehicle, all-round	0PGCU
<input type="checkbox"/>	Frame type, high	0P2TP
<input type="checkbox"/>	Vehicle type Tipper (KI)	0P2UN
<input type="checkbox"/>	Left-hand-drive	0P3AS
<input type="checkbox"/>	Right-hand traffic	0P3F5
<input type="checkbox"/>	Vehicle documents in German	0P2L6
<input type="checkbox"/>	Labelling in German	0P8NL
<input type="checkbox"/>	Cab position 720 mm (distance from frame lower edge to cab floor)	0PHBF

Registration

<input type="checkbox"/>	Vehicle approval, N3G class	0P3JS
<input type="checkbox"/>	Maximum speed limiter, 89 km/h, tolerance +1 km/h, electronic, engine speed regulation	0P2UJ
<input type="checkbox"/>	Regulation (EC) 595/2009, Euro VIe (heavy commercial vehicle emissions) fulfilled	0PJPC
<input type="checkbox"/>	Maximum vehicle noise level, 83 dB in acc. with UN/ECE-R 51.03	0PGTC
<input type="checkbox"/>	Height over cab, unloaded up to 4,000 mm	0PHA1
<input type="checkbox"/>	Swing out of vehicle rear up to 800 mm/1,000 mm with raised or steered last axle	0PHDB

Documents

<input type="checkbox"/>	Registration documentation, national	0P3AZ
<input type="checkbox"/>	Special confirmation, heavy load / municipal operation	0P3CK
<input type="checkbox"/>	L-plate and low-noise acceleration (in acc. with KDV 1967)	0P2E3

Application scope / transport tasks

<input type="checkbox"/>	Construction	0P6WH
<input type="checkbox"/>	090 Crane body	0P2R2
<input type="checkbox"/>	Temperate range, vehicle deployment, moderate	0P0G7
<input type="checkbox"/>	Case hardness of final drive Distribution	0P4F0

Lines, editions and packages

<input type="checkbox"/>	Construction site package	0PFXP
<input type="checkbox"/>	Trailer equipment preparation	0PFXN

Horizontal and vertical loads

<input type="checkbox"/>	26,000 kg permitted gross load, vertical, nat. appr.	0P5P2
<input type="checkbox"/>	28,000 kg permitted gross load, vertical, tech.	0P5TZ
<input type="checkbox"/>	28,000 kg permitted gross load, vertical, tech. Plus	0P8HN
<input type="checkbox"/>	9,000 kg permitted load on front axle, nat. appr.	0P5KX
<input type="checkbox"/>	9,000 kg permitted load on front axle, tech.	0P5LR
<input type="checkbox"/>	9,000 kg permitted load on front axle, tech. Plus	0P8EA



<input type="checkbox"/>	11,500 kg permitted load on rear axle NatZu	0P5G7
<input type="checkbox"/>	12,000 kg permitted load on rear axle, tech.	0P5IK
<input type="checkbox"/>	12,000 kg permitted load on rear axle, tech. Plus	0P8BP
<input type="checkbox"/>	7,500 kg permitted load on trailing axle, nat. appr.	0P5I6
<input type="checkbox"/>	8,000 kg permitted load on trailing axle, tech.	0P5JT
<input type="checkbox"/>	8,000 kg permitted load on trailing axle, tech. Plus	0P8CK
<input type="checkbox"/>	40,000 kg permitted gross train weight, national registration	0PBIO
<input type="checkbox"/>	68,000 kg permissible gross train weight TechH.	0PBW5
<input type="checkbox"/>	68,000 kg permitted gross train weight, Tech. Plus	0PBQN
<input type="checkbox"/>	24,000 kg trailer load, national registration	0P8SR
<input type="checkbox"/>	40,000 kg trailer load TechH.	0P8WY
<input type="checkbox"/>	40,000 kg trailer load, technical Plus	0P8UX
<input type="checkbox"/>	162kN D value	0P8YN
<input type="checkbox"/>	With the registered technical gross train weight, the maximum possible gradeability is 7 %	0P9A8

Notification texts

<input type="checkbox"/>	Note: Restricted steerability with engaged differential lock on front axle	0PFZN
<input type="checkbox"/>	Note: With increased permissible gross weight, increase in wear of driveline and reduced service life	0PFZP
<input type="checkbox"/>	Note: Max. 42,000 kg tech. permitted gross weight with engaged off-road reduction ratio in transfer case	0PFZS

Chassis

Vehicle frame (wheelbase, overhang, ...)

<input type="checkbox"/>	Main wheelbase, 3,600 mm	0P2ZD
<input type="checkbox"/>	Wheelbase between rear axle and trailing axle, 1,400 mm	0P3BT
<input type="checkbox"/>	Frame overhang, rear, 800 mm	0P3EU
<input type="checkbox"/>	Main frame side member thickness, 8 mm	0P0Y6
<input type="checkbox"/>	Vehicle rear, straight end of frame	0P0XT
<input type="checkbox"/>	Top coating, chassis	0P6YC

Exhaust system, air intake

<input type="checkbox"/>	Exhaust silencer, side, right, offset to the rear	0P1BI
<input type="checkbox"/>	Exhaust, bottom outlet	0P1BL

Battery cases, batteries, alternator

<input type="checkbox"/>	2 batteries, 12 V, 180 Ah, long-life (EFB), maintenance free	0PGB1
<input type="checkbox"/>	Three-phase alternator 28 V, 120 A, 3,360 W, LIN	0P1BZ
<input type="checkbox"/>	Medium battery box, 2 batteries	0P0WU
<input type="checkbox"/>	Battery box, left	0P0WO
<input type="checkbox"/>	Main battery switch, mechanical	0P0WF
<input type="checkbox"/>	Safety cut-out	0P1V2

Tanks and fuel line

<input type="checkbox"/>	Fuel tank capacity 300 l, left	0P4DK
<input type="checkbox"/>	Fuel tank, left, steel	0P4GK
<input type="checkbox"/>	Tank cross-section, right, medium	0P4HE
<input type="checkbox"/>	AdBlue tank capacity 35 l, left	0P8N3



<input type="checkbox"/>	AdBlue tank, left, plastic	0P4H1
<input type="checkbox"/>	Fuel tank cap, lockable, ventilated, for master key system	0P4H5
<input type="checkbox"/>	Cap for AdBlue tank, lockable	0P4GE

Frame attachments

<input type="checkbox"/>	Without underride protection, front	0P1FM
<input type="checkbox"/>	Without working platform	0P0VH
<input type="checkbox"/>	Without underride protection, side	0P1FG
<input type="checkbox"/>	Final cross member, with hole pattern 160 x 100 mm	0P1SB
<input type="checkbox"/>	Underride protection, rear, round	0P1FD
<input type="checkbox"/>	Wheel chock, two units, without retaining device, delivered loose	0P6WX
<input type="checkbox"/>	Body attachment bracket	0P0X5

Pneumatic brakes, compressed-air generation, brake system

<input type="checkbox"/>	Air compressor, 2-cylinder, 720 ccm, with economy system	0P8PH
<input type="checkbox"/>	Air dryer, heated	0P0B2
<input type="checkbox"/>	Compressed-air treatment, pneumatically controlled	0P0AB
<input type="checkbox"/>	Steel compressed-air tank	0P0XH
<input type="checkbox"/>	Electronic brake system (EBS)	0P0BL
<input type="checkbox"/>	Anti-lock braking system (ABS), Offroad, with additional off-road logic	0P0BF
<input type="checkbox"/>	Full brake assistant	0P0CM
<input type="checkbox"/>	MAN EVBec high-performance engine brake, stages possible	0P0BW
<input type="checkbox"/>	Retarder Eco Cool, speed-dependent, variable stages, energy eff., low heat input in coolant	0P0BQ
<input type="checkbox"/>	Drum brakes on front axle	0P1IA
<input type="checkbox"/>	Drum brakes on rear axle	0P1I5
<input type="checkbox"/>	Disc brakes on trailing axle	0P1I8
<input type="checkbox"/>	Parking brake control, in instrument panel	0P3KG
<input type="checkbox"/>	Parking brake with spring-type actuator on rear axles (incl. leading axle/ trailing axle)	0PGBL
<input type="checkbox"/>	Parking brake, on front axle(s), pneumatic, additional, exhaustible	0P0C1
<input type="checkbox"/>	MAN EasyStart immobiliser	0P1TF
<input type="checkbox"/>	Hill-climbing brake braking function	0P1TD
<input type="checkbox"/>	Brake lining thickness display, with brake lining wear warning	0P0BG
<input type="checkbox"/>	Harmonisation of brake lining wear	0P0BI
<input type="checkbox"/>	Disc brakes, protected, off-road use	0P1L1

Lights and acoustic signals on the chassis (rear lights, ...)

<input type="checkbox"/>	Rear lights	0P2AQ
<input type="checkbox"/>	Protective cover for rear lights	0P6XS
<input type="checkbox"/>	Emergency braking signal, hazard light activation, automatic	0P0CG
<input type="checkbox"/>	Light function test	0P2AD
<input type="checkbox"/>	Side marker lights, LED	0P2BJ

Driveline/running gear

Engine, radiator

<input type="checkbox"/>	Diesel engine MAN D2676 LFAF, 375 kW (510 hp) output, 2,600 Nm torque, Euro 6e	0PIA2
<input type="checkbox"/>	Engine, with on-board diagnosis, OBD-E	0PHZN
<input type="checkbox"/>	Fuel filter, heated, for fuels up to Cleanliness Class 21	0PHIF



<input type="checkbox"/>	Fuel pre-filter, with oil separator/water trap, with water sensor, heated	0P4XP
<input type="checkbox"/>	Engine oil with low-viscosity properties	0PGBN
<input type="checkbox"/>	Ventilation, crankcase, open	0P8PN
<input type="checkbox"/>	Anti-noise skirt, engine	0P2E7
<input type="checkbox"/>	Reduction of dust swirl through radiator fan	0P1YE
<input type="checkbox"/>	Engine cooler, normal length	0P4XX
<input type="checkbox"/>	Radiator protection, lower	0P1XE
<input type="checkbox"/>	Front radiator protection, grille	0P1VP
<input type="checkbox"/>	Engine oil dipstick and digital oil level gauge	0P0B6
<input type="checkbox"/>	Warning message for engine coolant level, with advance warning	0P0KA
<input type="checkbox"/>	Antifreeze, down to -32 °C	0P0AK
<input type="checkbox"/>	Cover for intercooler	0P1X4
<input type="checkbox"/>	Stationary regeneration for catalytic converter, executable only after warning	0PGCN

Gearbox, clutch

<input type="checkbox"/>	MAN TipMatic 12.28 OD, with retarder 35	0P5VX
<input type="checkbox"/>	Gearbox for increased percentage of overrun during driving operation	0PGCL
<input type="checkbox"/>	MAN TipMatic actuation, with drop arm, manual (DNR option, switching strategy option)	0P3KI
<input type="checkbox"/>	MAN Idle Speed Driving gearbox function	0P0ER
<input type="checkbox"/>	Rock-free gearbox function	0P0EV
<input type="checkbox"/>	MAN TipMatic Performance and Efficiency driving program, up to 70,000 kg	0PGBZ
<input type="checkbox"/>	MAN TipMatic Offroad gearbox shift strategy, up to 70,000 kg	0P0F4
<input type="checkbox"/>	MAN TipMatic Manoeuvre driving program, manoeuvring feature	0P0FI
<input type="checkbox"/>	Transfer case MAN G173 with on-road and off-road gear, neutral position	0P4XK
<input type="checkbox"/>	Transfer case lock management, electronic (VSM)	0P0FU
<input type="checkbox"/>	Single-disc clutch, 430 mm, dry	0P0DT

Wheels, tyres

<input type="checkbox"/>	Required tyre speed index J	0PFW2
<input type="checkbox"/>	Front axle tyres Continental 385/65R22.5 CROSS TRAC HS3 Steering-Road+Offroad TL	0PGXY
<input type="checkbox"/>	Rim type, front axle, steel, single-part	0P0P0
<input type="checkbox"/>	Rim size, front axle, 10-hole, 11.75x22.5	0P0NB
<input type="checkbox"/>	Wheel nut cover ring, front axle	0P0PR
<input type="checkbox"/>	Rear axle tyres Continental 315/80R22.5 CROSS TRAC HD3 Drive-S+G TL	0PDSR
<input type="checkbox"/>	Rim type, rear axle, steel, single-part	0P0OO
<input type="checkbox"/>	Rim size, rear axle, 10-hole, 9.00x22.5	0P0MU
<input type="checkbox"/>	Tyres for trailing axle Continental 385/65R22.5 CROSS TRAC HS3 Steering-Road+Offroad TL	0PGW2
<input type="checkbox"/>	Rim type, trailing axle, steel, single-part	0P0OT
<input type="checkbox"/>	Rim size, trailing axle, 10-hole, 11.75x22.5	0P0N4
<input type="checkbox"/>	Top coating, rims, steel, white-aluminium	0P6YL
<input type="checkbox"/>	Centring sleeves for rim mounting	0PHZW

Axles

<input type="checkbox"/>	6x4-4	0P3BA
<input type="checkbox"/>	Steering ratio, indirect	0P1JY
<input type="checkbox"/>	Steering oil tank with electrical measuring sensor	0P1JV
<input type="checkbox"/>	Front axle, 9,000 kg, planetary axle without drive shaft, straight, steered, not liftable	0P5ES
<input type="checkbox"/>	Front axle as planetary axle, driven, permanent	0P1GX
<input type="checkbox"/>	Mudguard, front axle	0P1AT



<input type="checkbox"/>	Rear axle, 13,000 kg, planetary axle without drive shaft, straight, not steered, not liftable	0P4ZN
<input type="checkbox"/>	Twin tyre on rear axle	0P1HN
<input type="checkbox"/>	Mudguard, rear axle, upper shell removable	0P1AM
<input type="checkbox"/>	Splash guard mat on mudguard, rear axle, longer at bottom	0P1XK
<input type="checkbox"/>	Trailing axle, 9,000 kg, not driven, straight, steered, liftable	0P4Z1
<input type="checkbox"/>	Single tyre on trailing axle	0P1HP
<input type="checkbox"/>	Mudguard, trailing axle with removable upper shell	0P1AR
<input type="checkbox"/>	Splash guard mat on mudguard, trailing axle, longer at bottom	0P1XO
<input type="checkbox"/>	Axle ratio, $i = 4.00$	0P0D2
<input type="checkbox"/>	Differential locks on driven rear axles	0P0DI
<input type="checkbox"/>	Differential locks on driven front axles	0P0DK
<input type="checkbox"/>	Warning buzzer when front axle locks are engaged	0P0DQ
<input type="checkbox"/>	Emergency steering pump	0P1KO
<input type="checkbox"/>	Digital axle load display (ALM) for air-sprung axles, cab	0P2IZ
<input type="checkbox"/>	Digital axle load display (ALM) for trailers/semitrailers, cab	0P2J1
<input type="checkbox"/>	Mudguard enlargement	0P1W5

Axle control system and suspension

<input type="checkbox"/>	Suspension type for front axles and driven rear axles, leaf/air (BL)	0P2YC
<input type="checkbox"/>	Control unit for electronically controlled air suspension (ECAS)	0P3K9
<input type="checkbox"/>	ECAS parameter input for automatic setting of normal level from 20 km/h	0P1KU
<input type="checkbox"/>	Lowering of air suspension to buffer with residual pressure control, automatic	0P1KQ
<input type="checkbox"/>	ECAS parametrisation, with auxiliary circuit for suppression of level control	0P1KW
<input type="checkbox"/>	Leaf-spring suspension on front axle, parabolic, 3-leaf, steel	0P1JE
<input type="checkbox"/>	Construction air suspension on rear axle	0P1IX
<input type="checkbox"/>	Air suspension on trailing axle	0P1J8
<input type="checkbox"/>	Spring load-bearing capacity front axle 9,500 kg	0P5C4
<input type="checkbox"/>	Spring load-bearing capacity of rear axle, 13,000 kg	0P5BV
<input type="checkbox"/>	Spring load-bearing capacity of trailing axle, 9,000 kg	0P5CE
<input type="checkbox"/>	Trailing axle relievable, moving-off aid with maximum speed limitation	0P1IM
<input type="checkbox"/>	Shock absorbers on front axle	0P1M4
<input type="checkbox"/>	Shock absorbers on rear axle	0P1LQ
<input type="checkbox"/>	Shock absorbers on trailing axle	0P1LV
<input type="checkbox"/>	Stabiliser, front axle	0P1LD
<input type="checkbox"/>	Stabiliser, rear axle	0P1LA
<input type="checkbox"/>	Stabiliser, trailing axle	0P1LL
<input type="checkbox"/>	Wishbone	0P6ZR

Cab

Cab and cab exterior

<input type="checkbox"/>	Top coating, cab	0P6YB
<input type="checkbox"/>	Top coating, bumper, steel	0P6YO
<input type="checkbox"/>	Top coating, step units	0P6X7
<input type="checkbox"/>	Top coating, mudguard, behind cab	0P6YF
<input type="checkbox"/>	Local transport cab NN	0P2DL
<input type="checkbox"/>	Cab mount, Comfort	0P1V9
<input type="checkbox"/>	Cab tilt mechanism, manual	0P1V6



<input type="checkbox"/>	Tilting roof, mechanical	0P1VW
<input type="checkbox"/>	Bumper, steel, 3 pieces	0P1SG
<input type="checkbox"/>	Front step, integrated, with grab option	0P1VE
<input type="checkbox"/>	Windscreen, composite safety glass, tinted	0P1X0
<input type="checkbox"/>	Sunblind, in front of windscreen	0P1WK
<input type="checkbox"/>	Wiper system for windscreen	0P1WG
<input type="checkbox"/>	Wiper activation, manual	0P1UL
<input type="checkbox"/>	Step unit, hinged	0P1V0
<input type="checkbox"/>	Central locking, with remote control	0P1WR
<input type="checkbox"/>	Vehicle key, 4 units	0P3JU
<input type="checkbox"/>	No door extension	0P1WW
<input type="checkbox"/>	Door labelling, according to trade tonnage of vehicle	0P2DQ
<input type="checkbox"/>	Door windows, tinted	0P1WO
<input type="checkbox"/>	Door window, safety glass	0P1WM
<input type="checkbox"/>	Construction-site rise with grab handles on cab roof, driver's side	0P1US
<input type="checkbox"/>	Cab rear wall, with window	0P1VB

Lights and acoustic signals on cab exterior (headlights, horn, ...)

<input type="checkbox"/>	Front headlights, H7	0P1ZN
<input type="checkbox"/>	Stone protection guard for front headlights, wide and fine mesh	0PICD
<input type="checkbox"/>	Daytime driving lights with rear lights, LED	0P2BQ
<input type="checkbox"/>	Fog lights, H7	0P2AH
<input type="checkbox"/>	Headlight beam regulator, manual	0P2AC
<input type="checkbox"/>	Driving-light control, manual	0P1ZF
<input type="checkbox"/>	Contour lights, LED, 2 units	0P2BS
<input type="checkbox"/>	Comfort indicator function, can be activated	0P1ZW
<input type="checkbox"/>	Turn signal lights, sides, bulb	0P1Z6
<input type="checkbox"/>	Compressed-air horn, 2 units, cab roof	0P1UW
<input type="checkbox"/>	Horn, two-tone, electrical	0P1W1
<input type="checkbox"/>	Revolving beacons, LED, yellow (individual LEDs light up in cascades, revolving)	0P2BD
<input type="checkbox"/>	2 revolving beacons on cab roof, 1 right and 1 left	0P2B3
<input type="checkbox"/>	Spotlights, 2 units, cab roof, 1 right and 1 left	0P1YM
<input type="checkbox"/>	Spotlight, halogen, white	0P1YY
<input type="checkbox"/>	Spotlight/manoeuvring light deactivation, speed-dependent	0P2C7
<input type="checkbox"/>	Preparation for loading area lighting	0P2A5

Mirrors and mirror replacements

<input type="checkbox"/>	Exterior rear-view mirror, electrically adjustable with manoeuvring aid	0P2CB
<input type="checkbox"/>	Mirror housing, not painted	0P2CP
<input type="checkbox"/>	Rear-view mirror arms, suitable for body width 2,500 mm to 2,600 mm	0P2CT
<input type="checkbox"/>	Kerb mirror, right, electrically adjustable	0P2CG
<input type="checkbox"/>	Front mirror, mechanical adjustment	0P2CJ
<input type="checkbox"/>	Preparation for rear-view camera, 2 units, one camera linked to reverse gear	0P2D3

Seats

<input type="checkbox"/>	Seat covers, fabric, Comfort	0P2PO
<input type="checkbox"/>	Comfort driver's seat, air-sprung, with lumbar support and shoulder adjustment	0P2P5
<input type="checkbox"/>	Driver's seat heating	0P2PX
<input type="checkbox"/>	Driver's seat arm rests	0P2OE



- Adjustment of seat belt height, driver's seat 0P4XQ
- Co-driver's seat, not sprung, length and backrest adjustment 0P2OQ
- Indicator, seat belt, 1st row of seats, acoustic and visual 0P8L1

Driver's workplace

- Multi-function steering wheel, adjustable height and angle 0P2GD
- Steering wheel, with parking position 0P2GE
- Steering lock, with electronic immobiliser 0P3K0
- Instrumentation, Basic km/h 0P3L3
- Tachograph, digital, with telecommunication (as per DSRC), CONTINENTAL 0P5DV
- Tachograph, calibrated 0P2KG
- Remote download for digital tachographs 0P2JJ
- Preparation for Toll Collect toll recording system 0P2MT
- Driving hours indicator, instrumentation 0P2MA
- Socket, cab centre, 2 units, 12 V and 24 V 0P2HX
- Stowage compartment, open with two USB sockets, 5 V, charging only, to the right of climate control panel 0PGT7
- 2 pull-out cup holders in instrument panel 0P2FA
- Plug-in ashtray, instrument panel in middle section, 1 unit 0P2FO
- Cigarette lighter 0P2IH
- Standard control field, inside of driver's door, with door open operated externally, 4 function buttons 0P3KE
- Preparation for radio with CB radio antenna on cab roof 0P2NK
- Single DIN slots, 4 units, roof space, front 0P2FJ

Cab air-conditioning system

- Air-conditioning system, Climatronic 0P2NT
- Ventilation, cannot be disabled, permanent and slight excess pressure in cab (reduces dust penetration) 0P2NX

Cab interior

- Colour scheme for interior styling, dark 0P2I6
- Interior styling analogous to colour scheme 0PGBT
- Windscreen roller blind, internal 0P2FE
- Roller blind for door windows, internal, mechanical, driver's side 0P2FH
- Curtain, cab rear wall window 0P2ID
- Interior light, central, LED, dimmable 0PGTZ
- 2 reading lights, LED, 1 on driver's side and 1 on co-driver's side 0PGTY
- Night lighting, LED, dimmable 0PGT2
- Entry lighting 0P2IO
- Door interior cladding, washable 0P2IA
- Drawer, 1 unit, instrument panel in middle section 0P2HJ
- Storage box, cab rear wall, 2 units, behind driver's and co-driver's sides 0P2F2
- Grab handle, above door, internal, 2 units, 1 right and 1 left 0P2G2
- Entry handles, standard 0PHPK

Accessories and tools

- Compressed-air connection, cab, with compressed-air hose and gun 0P2FM
- No jack 0P3F6
- Vehicle toolkit 0P2TX



<input type="checkbox"/>	Warning triangle, 1 units	0P3FI
<input type="checkbox"/>	First aid kit	0P3F3
<input type="checkbox"/>	Window cleaning set	0P3CI
<input type="checkbox"/>	Operator's manual in German, printed, additional	0P2JA
<input type="checkbox"/>	Hazard warning light, 1 units, with continuous light function	0P3FF

Intelligent Truck

Assistance systems

<input type="checkbox"/>	Tempomat (cruise control, CC)	0P1TR
<input type="checkbox"/>	Road speed limiter, adjustable, limiter (engine speed regulation)	0P0C3

Infotainment (radio,...)

<input type="checkbox"/>	ICS rotary/push controller (Interior Control System), with direct access buttons and touchpad	0P3KV
<input type="checkbox"/>	MMT infotainment system, Advanced Mid	0P2M0
<input type="checkbox"/>	MAN Advanced sound system	0P2MH
<input type="checkbox"/>	Europe and Russia navigation map	0P2MX
<input type="checkbox"/>	Online traffic for navigation function	0P2N4
<input type="checkbox"/>	MAN TeleMatics	0P2MO
<input type="checkbox"/>	Smartphone integration	0P2NE
<input type="checkbox"/>	MAN app integration	0P2MC
<input type="checkbox"/>	English additionally for display and MAN digital vehicle guide	0P2JQ

Bodies/interfaces

Interfaces to semitrailer (e.g. fifth-wheel coupling, brake connection,...)

<input type="checkbox"/>	Without trailer brake connection behind cab	0P1O3
<input type="checkbox"/>	No fifth-wheel coupling	0P1RJ

Interfaces to trailer (e.g. trailer coupling, brake connections,...)

<input type="checkbox"/>	Trailer coupling at final cross member, RINGFEDER type 5050 A	0P1N7
<input type="checkbox"/>	Trailer bar coupling for centre-axle trailer, on final cross member, 50 mm drawbar eye	0P1SM
<input type="checkbox"/>	2-line trailer brake connection, end of frame, centre, standard coupling	0P1NZ
<input type="checkbox"/>	Trailer socket, frame end, 24 V, 15-pin	0P1OM
<input type="checkbox"/>	Trailer socket for anti-lock brake system (ABS), end of frame	0P1O4

Ex works bodies and interfaces to bodies (e.g. tipper indicator...)

<input type="checkbox"/>	Preparation for engine start/stop facility, under front panel	0P0K8
<input type="checkbox"/>	Interface for data exchange with body (customer-specific control module) and intermediate engine speed (ZDR), behind front panel and behind cab	0PHPE
<input type="checkbox"/>	Display of workshop data for body, control module for ext. data exchange (customer-specific control module) with body functions	0P2J3
<input type="checkbox"/>	Tipper indicator, cab (symbols)	0P2M5
<input type="checkbox"/>	Operating device for tipper hydraulic, cab, with loading crane changeover	0P3KO
<input type="checkbox"/>	Electrical preparation for keypad, body control	0PINX

PTOs

<input type="checkbox"/>	PTO, gearbox-dependent, type NTX/10c, without flange, f=1.15, position approx. 3:30 o'clock	0P4RV
--------------------------	---	-------



<input type="checkbox"/>	PTO, gearbox-dependent, continuous operation	0P4VJ
<input type="checkbox"/>	PTO, gearbox-dependent, shiftable	0P4X9
<input type="checkbox"/>	Function parameters for PTO; gearbox-dependent, driving operation	0P4WP
<input type="checkbox"/>	Sector-specific parameterisation, general	0P4X0

Towing, recovery and lashing

<input type="checkbox"/>	Central coupling jaw, integrated in bumper/front cross member, with lock pin	0P1MK
--------------------------	--	-------

Colour

<input type="checkbox"/>	Top coating, chassis	GRAPHITE BLACK RAL 9011	W
<input type="checkbox"/>	Top coating, cab	TRAFFIC WHITE RAL 9016	N
<input type="checkbox"/>	Top coating, bumper, steel	TRAFFIC WHITE RAL 9016	A
<input type="checkbox"/>	Top coating, step units	TRAFFIC WHITE RAL 9016	A
<input type="checkbox"/>	Top coating, mudguard, behind cab	TRAFFIC WHITE RAL 9016	A

5897c3df-ab6c-4055-8da6-bc316686f02f